

EQUAL TEE, EQUAL CROSS & CAPS

ROLL GROOVE

VALVES
 GALVANISED MALLEABLE
 STAINLESS STEEL FITTINGS
 BLACK & GAL STEEL FITTINGS
 HIGH PRESSURE FITTINGS
 CAMLOCKS
 ROLL GROOVE
 BUTTWELD
 FLANGES

GVF CODE		DN SIZE (mm)	SUITS OD (mm)	L (mm)	WEIGHT (kg)
PAINTED	GALV				
RGT025	RGT025G	25	33.4	57	0.36
RGT032	RGT032G	32	42.2	70	0.63
RGT040	RGT040G	40	48.3	70	0.72
RGT050	RGT050G	50	60.3	70	0.88
RGT065	RGT065G	65	76.1	76	1.28
RGT080	RGT080G	80	88.9	85.5	1.86
RGT100	RGT100G	100	114.3	101	2.5
RGT125	RGT125G	125	141.3	124	4.68
RGT150	RGT150G	150	165.1	140	7.08
RGT200	RGT200G	200	219.1	175	11.43
RGT250	RGT250G	250	273	229	34.09
RGT300	RGT300G	300	323.9	254	47.37

GVF CODE		DN SIZE (mm)	SUITS OD (mm)	L (mm)	WEIGHT (kg)
PAINTED	GALV				
RGCR080	RGCR080G	80	88.9	85.5	2.33
RGCR100	RGCR100G	100	114.3	101	3.69
RGCR150	RGCR150G	150	165.1	140	9.68

GVF CODE		DN SIZE (mm)	SUITS OD (mm)	L (mm)	WEIGHT (kg)
PAINTED	GALV				
RGCAP050	RGCAP050G	50	60.3	23.5	0.22
RGCAP065	RGCAP065G	65	76.1	25.5	0.35
RGCAP080	RGCAP080G	80	88.9	25.5	0.5
RGCAP100	RGCAP100G	100	114.3	27	0.78
RGCAP150	RGCAP150G	150	165.1	27	1.6
RGCAP200	RGCAP200G	200	219.1	30.2	3.71

GVF CODE		DN SIZE (mm)	SUITS OD (mm)	L (mm)	WEIGHT (kg)
PAINTED	GALV				
RGCAP050B	RGCAP050BG	50	60.3	23.5	0.2
RGCAP065B	RGCAP065BG	65	76.1	25.5	0.32
RGCAP080B	RGCAP080BG	80	88.9	25.5	0.7
RGCAP100B	RGCAP100BG	100	114.3	27	0.94
RGCAP150B	RGCAP150BG	150	165.1	27	1.93

MATERIALS	
Body	Ductile Iron
Gasket	EPDM

SPECIFICATIONS
Cold Working Pressure
1600 kPa / 300 PSI

STANDARD
Material
ASTM A536
Design
AWWA C606

